



## DELTA JEEP® QUAD-BAR XENON HEADLAMP KIT Headlamp Replacement for JEEP Wrangler JK 1997 - 2012

P/N 01-1198-50X

### INSTALLATION INSTRUCTION

1. Remove your existing headlamps by first unscrewing the grill fascia surrounding the headlamp.
2. Remove the ring holding the headlamp with (4) four screws. You will no longer need it.
3. Unplug the socket in the back of the headlamp element and plug in the H13 adaptor (provided for JK models).
4. Plug in your DELTA Quad-Bar headlamp element into the other end of the adaptor and screw back to the headlamp bucket using your existing screws.



5. Re-install the grill fascia by pushing in the screws in position.
6. DELTA Quad-Bar headlamps are equipped with "City Lights" (small, low wattage bulbs on the side of your reflector). These "City Lights" could be used as extra parking lights, daytime running lights or directional lights (if you replace them with amber color). For parking lights, just tap your City Light to your existing parking light. For DRL application, you may tap into your ignition switch line. For directional lights, replace the miniature bulbs with amber color bulbs and tap each to respective factory directional light wire lead. (See attached supplemental instruction).
- 7.

**NOTE: When installing be sure rubber boot is snugly fitting over the reflector providing a good seal against moisture. In the event any moisture is trapped inside the headlight causing it to steam up, please follow these procedures: Peel back the rubber boot and carefully remove the bulb by releasing first the bulb spring. Allow vapor to escape by holding the headlight in sunlight or using a hair dryer. When completed, assemble the bulb and re-seal the boot around the reflector.**

**HAPPY FOUR WHEELING!**

**DELTA TECH INDUSTRIES, LLC - Ontario, CA 91761, U.S.A.**

Web: [www.deltalights.com](http://www.deltalights.com) E-mail: [tech@deltalights.com](mailto:tech@deltalights.com)



ASSEMBLED IN USA  
EUROPEAN OPTICS